

NP2160 Touch POS Terminal



The Nexa NP2160 is the flexible and reliable solution for POS applications both large and small. The low profile base is specifically designed for space-limited applications.

It features a quad core Intel J1900 2.42 GHz CPU.

Bezel free front panel rated IP65.

It has a large selection of ports, allowing easy connection of the large number of peripherals often found at the point of sale.

The NP2160 and its low profile base can be mounted on a wall. The base includes Vesa mounting holes.

The Nexa NP2160 includes 3 years warranty, giving you peace of mind.



Can fold down
to 6.5cm



Many ports
included

3

year warranty

Panel

LCD Size	15"
Resolution	1024 x 768
Luminance	250 cd/m ²
Touch Screen	10-points P-CAP type

System

CPU	Fanless Intel J1900 2.42GHz Quad Core
Memory	SO-DIMM DDR3L 1067/1333MHz x 1, 2GB, upgradeable to 8GB
Hard Disk Drive	2.5" SATA HDD / SSD x 1

I/O

USB	4x USB2.0 port, USB 3.0 x1
COM	RS-232 x 3, DB-9 Pin9 with RI/5V/12V selectable by BIOS. COM 1: RS-232, RJ-50 with convert to DB-9 cable COM 2: RS-232, RJ-50 with convert to DB-9 cable COM 3: RS-232/422/485, DB-9 COM 6: RS-232, Internal reserved for 2x20 VFD Customer Display
Ethernet	1x RJ-45 10/ 100/ 1000 Mbps
VGA	1x BD-15 2nd VGA port
Cash Drawer	1x RJ-11 port 12V / 24V DC

Physical

Dimensions	36 x 28.9 x 25.2 cm (14.2 x 11.4 x 9.9 inch)
Weight	5 kg, 11 lb / 6.5 kg, 14 lb
Mounting	75mm x 75mm VESA
Operating Temperatures	0°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	20% to 85% RH (non condensing)

Accessories	MSR, VFD, 10" Customer Facing LCD
-------------	-----------------------------------